

**PART NUMBER:** XA-LVRT50**DESCRIPTION:** 1/2 in. High Strength Stainless Seismic Restraint**SPECIFICATIONS**

SUGG MAX LOAD: 375 lbs.

STUD DIAMETER: 1/2 in.

LOCKNUT/BOLT TORQUE: 55 ft. lbs.

MAX LEV EXTENSION: 1.00 in.

**DISCLAIMER:** ATLAS CASTERS MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, WITH RESPECT TO THE SUFFICIENCY OR FITNESS OF THIS PRODUCT FOR A PARTICULAR APPLICATION. WE EXPRESSLY ADVISE THAT ANY USE OF OR RELIANCE UPON THIS PRODUCT IS AT THE RISK OF THE USER AND THAT ATLAS CASTERS SHALL NOT BE LIABLE FOR ANY DAMAGE OR INJURY TO PERSONS OR PROPERTY ARISING FROM ITS USE.

LOCAL CONDITIONS AND REGULATIONS MAY REQUIRE ADDITIONAL PROFESSIONAL INVESTIGATIONS, MODIFICATIONS, OR SAFEGUARDS TO MEET SITE, EQUIPMENT, OR COMPANY-SPECIFIC REQUIREMENTS. SPECIFIC APPLICATIONS WILL CONTAIN VARIABLES UNKNOWN TO OR BEYOND THE CONTROL OF ATLAS. AS A RESULT, ATLAS CANNOT WARRANT THAT THE APPLICATION OF THIS PRODUCT WILL PRODUCE THE TECHNICAL RESULT OR MARGIN OF SAFETY ORIGINALLY INTENDED.

**!!! WARNINGS !!!**

1. SECURE LEVELER TO RESTRAINT WITH LOCKNUT.
2. DO NOT EXCEED MAXIMUM LEVELER EXTENSION.
3. USE STAINLESS HEX STUDS WITH RESTRAINTS.

